

SAP Fiori Mobile (v2.1.x)

Introduction

What are hybrid mobile apps?

Hybrid mobile apps are web applications wrapped up their own browser which can run on any of the mobile platforms (Android, iOS, Windows etc.). The big advantage of a hybrid app is that it has a single code base, whereas a native app must be re-written for each platform.

Apache [Cordova](#) is an open-source framework for developing hybrid apps. To use native features (beyond those already available via hmtl5,) apps can make use of plugins. These plugins handle the platform-specific code and are available for single or multiple platforms. Plugins are available to access the GPS, accelerometer or camera, for example.

SAP have written their own plugins, branded as [Kapsel](#), to handle things like logon and offline OData. These bring an enterprise flavour to hybrid apps.

What is Fiori Mobile?

Until recently SAP's recommended approach was to use the Hybrid Application Toolkit (or HAT) in order to build hybrid apps. The app build took place on the developer's PC or Mac. The HAT gained a reputation for being tricky to set up and that hindered the use of hybrid apps within the SAP ecosystem.

Fiori Mobile has at its core a cloud-build service, so there is no need to install the HAT. We can trigger the build from Web IDE. We specify the (already deployed) Fiori app(s) that we want to package and after a few minutes we can download the .apk (for Android) and .ipa (for iOS) files ready to be installed on mobile devices.

Does it work?

The cloud build service works well. It typically build for both platforms in about 8 minutes without issues. There have only been a couple of occasions when builds failed due to technical problems.

There are some facets to the technology which don't feel mature yet. One area is the offline OData features. When using Fiori Mobile things work differently to the more conventional hybrid and native apps. One example would be the destinations, because Fiori Mobile apps use a generated destination which reference the SAP Cloud Platform (CP) portal service.

My point is not that offline OData seems immature, rather that the offline features can be tricky when used with Fiori Mobile apps. We are still receiving assistance from SAP to get the offline features of our app optimised. This is a shame, because shared data and the handling of delta requests, for example, are two features which justify the 'middleware' approach to offline that SAP have taken.

Authentication has also been a challenge. On a previous project I used the Fiori Client in conjunction with SAP Cloud Identity (now officially SAP Cloud Platform Identity Authentication). The Fiori Client stored the username and password on the device so that the user didn't need to enter them every time their session timed out. We haven't achieved that yet with our Fiori Mobile app.

Account and Services

If you have production account browse on HCP Cockpit and log in. If you use trial account log in here

As we said before there is two ways to build SAP Fiori mobile application:

1. Using **Fiori Mobile Service**. Note that this service have been discontinued from March 31, 2018. Strategic features available in the mobile service for SAP Fiori have been incorporated into SAP Cloud Platform mobile service for development and operations. However you can use this service if you have old account that already has enabled that service. Using this service require two other services to be enabled: **Portal Service** and **SAP Web IDE Full-Stack Service**.

SAP Cloud Platform Cockpit

Overview

Applications

Services

Solutions

SAP HANA / SAP ASE

Connectivity

Security

Repositories

Usage Analytics

Members


Platform Roles

Useful Links

Internet of Things

Remote Data Sync


Enabled

Synchronize data between remote databases and a cloud SAP HANA database.

Mobile

Mobile Services, preview


Enabled

Run integration and regression tests and explore new mobile features. NOT FOR PRODUCTIVE USE.

Runtimes & Containers

HTML5 Applications


Enabled

Develop and run HTML5 applications in a cloud environment.

User Experience

Portal

Enabled

Create role based, multi-channel sites to access business apps and content.

Services

Solutions

SAP HANA / SAP ASE >

Connectivity >

Security >

Repositories >


Usage Analytics

Members

Platform Roles

Remote Data Sync

Enabled




Synchronize data between remote databases and a cloud SAP HANA database.

Mobile

Mobile Services, preview


Enabled



Run integration and regression tests and explore new mobile features. NOT FOR PRODUCTIVE USE.

SAP Fiori Mobile

Enabled



Optimize, build, manage, and monitor SAP Fiori apps on mobile devices.

Services

Solutions

SAP HANA / SAP ASE >

Connectivity >

Security >

Repositories >

Usage Analytics

Members


Platform Roles

All: 24

Data Management

SAP ASE


Enabled



Create and consume SAP ASE databases.

SAP HANA

Enabled




Create and consume SAP HANA databases.

Data Privacy & Security

Authorization & Trust Managem...


Enabled



Manage application authorizations and trusted connections to identity providers.

Keystore Service


Enabled



Manage cryptographic keys and certificates.

OAuth 2.0

Enabled




Protect applications and APIs with OAuth 2.0.

Developer Experience

Git Service


Enabled



Store and version source code in Git repositories.

Java Debugging


Enabled



Debug your Java application even through networks with high latency.


SAP Web IDE Full-Stack

Enabled



Create and extend SAP full-stack applications for browsers and mobile devices.


2. Using **HAT** (Hybrid Application Toolkit) extension in **SAP Web IDE Full-Stack Service**. Using this extension require **Mobile Services** to be enabled.



Create Fiori Launchpad

If we use SAP Fiori Mobile Service to build mobile application first we need to create and publish site where application will be deployed. Otherwise if we use HAT skip this step and continue with [Create Fiori Project](#)

Go to **Portal Service** and create new Site Directory



A popup will be displayed. Enter your **Site Name**, choose **SAP Fiori Launchpad** as Template Source and click Create

Create Site

*Site Name

cmbSDKTestSite

Available Site Templates

Search

Template Source

All

Starter Site

Basic Layout Set

Admin Site


SAP Fiori Launchpad


Create

Close

Following this you will be redirected to SAP Fiori Configuration Cockpit. Close the tab and go back to Admin Space for Portal Service.

Now we need to Publish this Site and Set as default.





Create Fiori Project

Once we create and publish cmbSDKTestSite we can create our Fiori project (if we use Fiori Mobile Service to build mobile application, otherwise if we use HAT we don't need to publish site on Launchpad and creating Fiori project will be our first step).

Go to Services tab again, open SAP Web IDE Full-Stack service, and click on Go to Service



Service: SAP Web IDE Full-Stack - Overview

Enabled

Service Description

With SAP Cloud Platform Web IDE Full-Stack, you can easily develop, test, build, and deploy apps for business users. Create applications rapidly and deliver an outside-in architecture. You can also build SAP Fiori apps, create new SaaS solutions, extend SAP S/4HANA cloud solutions, and build IoT apps for SAP Leonardo, using the UI development toolkit for HTML5, the SAP HANA toolset, and Java programming language and technologies. Integrate with SAP Cloud Platform, such as SAP Fiori Cloud apps, Git integration, mobile services, IoT services, and more.

Take Action

[Configure Service](#)

[Logs](#)

[Go to Service](#)



A new tab will be opened. From here we will start to create our Fiori project.

- Click on New Project from Template

General Information
Tile Configuration
Assignment
Confirmation

Register to SAP Fiori Launchpad

General Information

*Provider Account portal (flpnwc) ▼

*Application Name [?] MyFirstFioriApp.MyFirstFioriApp.MyFirstFioriApp

Description

Intent

<input type="checkbox"/>	Semantic Object	Action
<input type="checkbox"/>	MyFirstFioriApp	Display

[More information on intent properties.](#)

- Choose SAPUI5 Application from Template Selection

Template Selection
Basic Information
Template Customization
Confirmation

New SAPUI5 Application

Template Selection

Search Environment Category Sort By SAPUI5 Version

Neo Featured Sort by name SAP Innovation (1.66) ▼

List Report Application

SAP Fiori Master-Detail Application

SAP Fiori Worklist Application

SAP Fiori Worklist Application OData V4

SAPUI5 Application

Creates a SAPUI5 project including an optional view. You can choose one of the following view types: XML, JSON, JavaScript, and HTML. For more information, see the relevant [Fiori Design Guidelines](#).

- Set your Project Name and Namespace

Template Selection
Basic Information
Template Customization
Confirmation

New SAPUI5 Application

Basic Information

Project Name*

App Descriptor Data

Namespace*

- Choose the View Type and set the View Name. In our sample we will use XML View. Click Finish and your Fiori project is created.

Template Selection
Basic Information
Template Customization
Confirmation

New SAPUI5 Application

Template Customization


Initial View Details

View Type*

View Name

How to use cmbSDK cordova plugin

In the SAP Web IDE Workspace we can see all files that our Fiori project includes.



Open *Component.js* file.

Component.js is the first point of our application, we can say that it serves as index which encapsulates all our applications details, i.e. view names, routing details, main view, applications type(Full Screen or SplitApp), application service configuration etc..

Here in **init** function we will configure our plugin. Set properties that we need, set callback functions, call some methods, etc..

```
sap.ui.define([
    "sap/ui/core/UIComponent",
    "sap/ui/Device",
```

```

        "MyFirstFioriApp/MyFirstFioriApp/model/models"
    ], function (UIComponent, Device, models) {
        "use strict";

        var oEventBus = sap.ui.getCore().getEventBus();
        var scannerIsInitialized = false;

        return UIComponent.extend("MyFirstFioriApp.MyFirstFioriApp.Component", {

            metadata: {
                manifest: "json"
            },

            /**
             * The component is initialized by UI5 automatically during the startup of the app and
            nd calls the init method once.
             * @public
             * @override
             */
            init: function () {
                // call the base component's init function
                UIComponent.prototype.init.apply(this, arguments);

                // enable routing
                this.getRouter().initialize();

                // set the device model
                this.setModel(models.createDeviceModel(), "device");

                if (!scannerIsInitialized) {

                    scannerIsInitialized = true;
                    window.readerConnected = 0;
                    window.scannerActive = false;

                    cmbScanner.addOnResume(function (result) {
                        cmbScanner.setAvailabilityCallback((readerAvailability) => {
                            if (readerAvailability === cmbScanner.CONSTANTS.AVAI
LABILITY_AVAILABLE) {
                                oEventBus.publish("ScanView", "SetConnection
Status", {
                                    statusText: "AVAILABLE"
                                });
                                cmbScanner.connect((result) => {});
                            } else {
                                oEventBus.publish("ScanView", "SetConnection
Status", {
                                    statusText: "NOT AVAILABLE"
                                });
                            }
                        });
                        if (Device.os.android) {
                            cmbScanner.connect((result) => {});
                        }
                    });

                    cmbScanner.addOnPause(function (result) {
                        if (Device.os.android) {
                            cmbScanner.disconnect();
                        }
                        cmbScanner.setAvailabilityCallback();
                    });
                }
            }
        });
    }

```

```

    });

    cmbScanner.setPreviewContainerPositionAndSize(0, 0, 100, 50);

    cmbScanner.setConnectionStateDidChangeOfReaderCallback((connectionState) => {
        if (connectionState === cmbScanner.CONSTANTS.CONNECTION_STATE_CONNECTED) {
            oEventBus.publish("ScanView", "SetConnectionStatus", {
                statusText: "CONNECTED"
            });
            if (window.readerConnected !== connectionState) {
                cmbScanner.setSymbologyEnabled("SYMBOL.DATAMATRIX", true);
                cmbScanner.setSymbologyEnabled("SYMBOL.C128", true);
                cmbScanner.sendCommand("SET TRIGGER.TYPE 2")
            }
        } else if (connectionState === cmbScanner.CONSTANTS.CONNECTION_STATE_DISCONNECTED) {
            oEventBus.publish("ScanView", "SetConnectionStatus", {
                statusText: "DISCONNECTED"
            });
        } else if (connectionState === cmbScanner.CONSTANTS.CONNECTION_STATE_CONNECTING) {
            oEventBus.publish("ScanView", "SetConnectionStatus", {
                statusText: "CONNECTING"
            });
        } else if (connectionState === cmbScanner.CONSTANTS.CONNECTION_STATE_DISCONNECTING) {
            oEventBus.publish("ScanView", "SetConnectionStatus", {
                statusText: "DISCONNECTING"
            });
        }
        window.readerConnected = connectionState;
    });

    cmbScanner.setAvailabilityCallback((readerAvailability) => {
        if (readerAvailability === cmbScanner.CONSTANTS.AVAILABILITY_AVAILABLE) {
            oEventBus.publish("ScanView", "SetConnectionStatus", {
                statusText: "AVAILABLE"
            });
            cmbScanner.connect((result) => {});
        } else {
            oEventBus.publish("ScanView", "SetConnectionStatus", {
                statusText: "NOT AVAILABLE"
            });
        }
    });

    cmbScanner.setActiveStartScanningCallback((result) => {
        if (result === true)
            window.scannerActive = true;
    });

```

```

        else
            window.scannerActive = false;
        });

        cmbScanner.setPreviewOptions(cmbScanner.CONSTANTS.PREVIEW_OPTIONS.DE
FAULTS | cmbScanner.CONSTANTS.PREVIEW_OPTIONS.HARDWARE_TRIGGER);

        cmbScanner.setCameraMode(cmbScanner.CONSTANTS.CAMERA_MODES.NO_AIMER)
;

        var sdkKEY = "";
        if (Device.os.android)
            sdkKEY = this.getModel("i18n").getProperty("MX_MOBILE_LICENS
E_ANDROID");
        else
            sdkKEY = this.getModel("i18n").getProperty("MX_MOBILE_LICENS
E_iOS");

        cmbScanner.registerSDK(sdkKEY);

        cmbScanner.loadScanner(0, (result) => {
            cmbScanner.connect((result) => {});
        });

        oEventBus.subscribe("Component", "LoadScanner", this.loadScanner, th
is);
    },
    loadScanner: function (sChanel, sEvent, oData) {
        cmbScanner.disconnect((result) => {
            cmbScanner.loadScanner(oData.selectedDevice, (result) => {
                cmbScanner.connect((result) => {});
            });
        });
    },
    onExit: function () {
        oEventBus.unsubscribe("Component", "LoadScanner", this.loadScanner, this);
        cmbScanner.disconnect();
        cmbScanner.setAvailabilityCallback();
    }
});
});

```

cmbScanner is an object that represents our plugin. With this object we can access all [API methods](#) and Constants from our plugin.

- **scannerIsInitialized** - variable to make sure that we set some functions for initialization only one time
- **window.readerConnected** - global variable that is changed every time when the reader connection state is changed
- **window.scannerActive** - global variable that shows us if scanning is active or not
- **cmbScanner.addOnPause** - in this method we disconnection from reader device on Android (on iOS this is handled automatically), and stop listening to availability changing
- **cmbScanner.addOnResume** - in this method we try to connect with reader device again and set callback for availability changing

- **cmbScanner.setPreviewContainerPositionAndSize** - to set the size and position of the preview container. Learn more [here](#).
- **cmbScanner.setConnectionStateDidChangeOfReaderCallback** - all **connect/disconnect** events should be handled within the callback function set with this API method. If connection state is **connected** we set some reader device settings with [API methods](#) or directly with [sendCommand\(\)](#) method. Here in this example we enable symbologies and set trigger type. Also here we should Licensing the SDK. We will speak about this later in this section
- **cmbScanner.setAvailabilityCallback** - to monitor for availability of the MX device. If MX device is available we try to connect. Learn more [here](#).
- **cmbScanner.setActiveStartScanningCallback** - to monitor the state of the scanner. Learn more [here](#).
- **cmbScanner.loadScanner** - to get a scanner up and running. Learn more [here](#).

Here we are only configuring reader device, handling connections, availability, etc.. We will do scanning and getting results in other views. If we want to notify users about every connection state changed or other info about reader device we will be using [EventBus](#) sap object. With this object we can publish function and call them from any view in the application. In this example on connection state changed with EventBus we are calling **SetConnectionStatus** function that is implemented in view where scanning is performed and set label text to show user current connection state.

Now open **ScanView.view.xml** and add this code:

```
<mvc:View controllerName="MyFirstFioriApp.MyFirstFioriApp.controller.ScanView" xmlns:mvc="sap.ui.cor
e.mvc" displayBlock="true" xmlns="sap.m"
    xmlns:core="sap.ui.core">
    <Shell id="shell">
        <App id="app">
            <pages>
                <Page id="page" title="{i18n>title}">
                    <subHeader>
                        <Toolbar id="__toolbar2" width="100%">
                            <content>
                                <FlexBox id="__box0" width="100%" al
                                ignedContent="Center" alignItems="Start" direction="Column" fitContainer="true" justifyContent="Center
                                ">
                                    <items>
                                        <Select id="selectAc
                                        tiveDevice" items="{/Devices}" textAlign="Center" selectedKey="0" change="activeDeviceChanged">
                                            <core:Item t
                                            ext="{text}" key="{key}"/>
                                        </Select>
                                    </items>
                                </FlexBox>
                                <Label id="lblStatus" text="DISCONNE
                                CTED" width="100%" textAlign="End" design="Bold"/>
                            </content>
                        </Toolbar>
                    </subHeader>
                    <content>
                        <FlexBox id="flexBoxContainer" width="100%" alignCon
                        tent="Start" alignItems="Start" direction="Column" fitContainer="true"/>
                    </content>
                </Page>
            </pages>
        </App>
    </Shell>
</mvc:View>
```




```

</mvc:View>
</Shell>
</App>
</pages>
</Page>
</footer>
</Toolbar>
</content>
<Button id="btnScan" press="btnScanP
ress" text="Scan" width="100%"/>
</content>
</Toolbar id="__toolbar1" width="100%">
</footer>

```

You can design view with CodeEditor or with LayoutEditor.



After that open **ScanView.controller.js** and add this code

```

sap.ui.define([
    "sap/ui/core/mvc/Controller"
], function (Controller) {
    "use strict";

    var oEventBus = sap.ui.getCore().getEventBus();
    var oModel = new sap.ui.model.json.JSONModel();
    oModel.setData({
        Devices: [{

```

```

        key: "0",
        text: "MX Device"
    }, {
        key: "1",
        text: "Mobile Camera"
    }]
});

return Controller.extend("MyFirstFioriApp.MyFirstFioriApp.controller.ScanView", {
    onInit: function () {
        this.getView().setModel(oModel);
    },

    onAfterRendering: function () {
        window.scannerActive = false;
        switch (window.readerConnected) {
            case cmbScanner.CONSTANTS.CONNECTION_STATE_CONNECTED:
                this.getView().byId("lblStatus").setText("CONNECTED");
                break;
            case cmbScanner.CONSTANTS.CONNECTION_STATE_DISCONNECTED:
                this.getView().byId("lblStatus").setText("DISCONNECTED");
                break;
            case cmbScanner.CONSTANTS.CONNECTION_STATE_CONNECTING:
                this.getView().byId("lblStatus").setText("CONNECTING");
                break;
            case cmbScanner.CONSTANTS.CONNECTION_STATE_DISCONNECTING:
                this.getView().byId("lblStatus").setText("DISCONNECTING");
                break;
            default:
                this.getView().byId("lblStatus").setText("UNKNOWN");
                break;
        }
        oEventBus.subscribe("ScanView", "SetConnectionStatus", this.setConnectionSta
tus, this);

        cmbScanner.setResultCallback((result) => {

            if(result && result.readResults && result.readResults.length > 0){

                result.readResults.forEach((item, index) => {

                    if (item.goodRead == true) {
                        //Perform some action on barcode read
                        //example:
                        var verticalLayoutContainer = new sap.ui.layout.VerticalLayout(null, {
                            width: "100%"
                        }).addStyleClass("sapUiSmallMarginTop");
                        verticalLayoutContainer.addContent(new sap.m.Label({
                            text: item.symbologyString + ":",
                            textAlign: "Begin",
                            design: "Bold"
                        }).addStyleClass("sapUiSmallMarginBegin"));
                        verticalLayoutContainer.addContent(new sap.m.Text({
                            text: item.readString,
                            textAlign: "Begin"
                        }).addStyleClass("sapUiSmallMarginBegin"));
                        this.getView().byId("flexBoxContainer").addItem(vert
icalLayoutContainer);
                    }
                    else{

```

```

//Perform some action when no barcode is read or just
t leave it empty
    }
    });
}
    });
},

btnScanPress: function () {
    if (window.readerConnected === cmbScanner.CONSTANTS.CONNECTION_STATE_CONNECTED) {
        if (window.scannerActive === true) {
            cmbScanner.stopScanning();
        } else {
            cmbScanner.startScanning();
        }
    }
},

setConnectionStatus: function (sChannel, sEvent, oData) {
    this.getView().byId("lblStatus").setText(oData.statusText);
},

activeDeviceChanged: function () {

    cmbScanner.disconnect((result) => {
        oEventBus.publish("Component", "LoadScanner", {
            selectedDevice: parseInt(this.getView().byId("selectActiveDevice").getSelectedKey())
        });
    });
},

onExit: function () {
    oEventBus.unsubscribe("ScanView", "SetConnectionStatus", this.setConnectionStatus, this);
    if (window.readerConnected === cmbScanner.CONSTANTS.CONNECTION_STATE_CONNECTED) {
        if (window.scannerActive === true) {
            cmbScanner.stopScanning();
        }
    }
    cmbScanner.setResultCallback((result) => {
        return false;
    });
}
});
});
});

```

In this view we have a Scan button to [startScanning\(\)/stopScanning\(\)](#) and [cmbScanner.setResultCallback](#) to handle successful scan results.


Build Fiori Mobile Application

In this section we will explain how to build Fiori Mobile Application (generate .ipa and .apk


files).

1. Using **HAT** (Hybrid Application Toolkit)

- First we need to enable **HAT** extension in SAP Web IDE Workspace. Open Tools->Preferences:



- Navigate to Extensions section and search for HAT extension:




By default HAT extension is disabled. Enable HAT extension and click Save. After enabling we will need to refresh SAP Web IDE.

Extensions

Enable the SAP Web IDE extensions you want, save, and refresh the browser.

HAT All Categories All States

2 results




Workflow Editor

You can model and deploy workflows that help in automating process steps.

V 1.51.0 [More Information](#)

☐ OFF



Hybrid App Toolkit


You can create hybrid mobile apps using Apache Cordova and SAP Mobile Platform SDK in SAP Web

V 1.32.3 [More Information](#)

☒ ON


Save

- After enabling HAT go again in Tools->Preferences. If you have both Fiori Mobile and Mobile Services enabled you will have options to select one that will be used as Cloud Build Service. Please choose **Mobile Services** and click Save:




If you don't see these radio buttons you don't need to do anything. **Mobile Service** will be enabled by default.

- Now right click on project root and you will see Mobile section. Click **Enable as Hybrid Mobile Project**



- You can see that some new files are added in our project that allow us to build this project as mobile application. Before build we need to add our **cmbsdk-cordova** plugin. Click on Select Cordova Plugins, find cmbsdk-cordova plugin from public plugins and add in this project. Don't forget to click Save when you add plugin.



Select Cordova Plugins

Selected (9)

Public (1)

Kapsel (20)

Select Platform



▼

cmbosdk-cordova

ⓧ


🔍

↕


Plugin ID	Platform	Version	Description	Last Updated On	Actions
cmbosdk-cordova		1.2.14	CMB Scanner Cordova Plugin	6 Jun 2019	<div><div>Add</div><div>View Details</div></div>

Save

Close



- We are ready to build our mobile application and generate .ipa and .apk files. Click on **Build Packaged App** from Mobile menu.



- Set your application details

App Info
Platform
Push Notification
Confirmation

Configure Mobile Build Settings

App Info

*App Name	<input type="text" value="MyFirstFioriApp"/>	App Version (?)	<input type="text" value="Leave blank for default versioning"/>
Description	<input type="text" value="Enter app description"/>	Landscape Splash	<input type="text" value="Upload a landscape app splash"/> ...
Icon	<input type="text" value="Upload an app icon"/> ...	Portrait Splash	<input type="text" value="Upload a portrait app splash"/> ...

152px X 152px

2048px X 1536px

1536px X 2048px

Previous

Next

- Choose platform or both iOS and Android platforms, select signing profiles (or create one if you don't have) and set some common options

App Info


Platform


Push Notification

Confirmation

Configure Mobile Build Settings

Platform

☒ iOS 

☒ Android 

Signing Profile

iOSSapAppDev

▼

Signing Profile


AndroidSapAppDev

▼

Minimum OS Version

11.0


▼


Minimum OS Version 


5.0

▼

Common Options

☐ Build debug-enabled binaries 

☒ Disable privacy screen 

☐ Save Xcode and/or Android Studio projects 

Packaged SAPUI5 Version

1.64.1

▼

Previous

Next

- Start building process

App Info

Platform

Push Notification

Confirmation

Configure Mobile Build Settings

Confirmation

Click the Build button to save the app settings and start building the project.

When the build finishes, a result dialog will show. If the build succeeds, you will be able to download and install the app on your device.

Previous

Build


- When building process is finished popup from where you can download .ipa and .apk files will be shown



2. Using **Fiori Mobile Service**

Before we start to build our Fiori Mobile Application with Fiori Mobile Service we need to deploy our project on SAP HANA Cloud Platform.

- Right click on project folder then select Deploy and choose Deploy to SAP Cloud Platform



- Set application details and click Deploy

Deploy Application to SAP Cloud Platform

A build will be triggered for the project. The build results will be deployed.

Application Details

☒ Deploy a new application
 ☐ Update an existing application

*Account [Redacted] Get Accounts

Project Name MyFirstFioriApp

*Application Name myfirstfioriapp

Version Management

*Version 1.0.0
☒ Activate

Deploy
Cancel

- After a successful deploy, the next step is to Register to SAP Fiori launchpad that we've created in the previous section.

Successfully Deployed

Version 1.0.0 has been created.

[Open the active version of the application](#)

[Open the application's page in the SAP Cloud Platform cockpit](#)

You can now register the application to SAP Fiori launchpad.

Register to SAP Fiori launchpad
Close

- Choose account and set application name

General Information Tile Configuration Assignment Confirmation

Register to SAP Fiori Launchpad

General Information

*Provider Account portal (flpnc) v

*Application Name [?] MyFirstFioriApp.MyFirstFioriApp.MyFirstFioriApp

Description

Intent

	Semantic Object	Action
<input type="checkbox"/>		
<input type="checkbox"/>	MyFirstFioriApp	Display

[More information on intent properties.](#)

- Set Type (Static by default), set Title, and Subtitle

General Information Tile Configuration Assignment Confirmation

Register to SAP Fiori Launchpad

Tile Configuration

*Type Static

*Title cmbSDK Fiori App

Subtitle Sample

Icon sap-icon://approvals

- Choose Site that we create before, catalog, and group (sample catalog and group is created by default)

General Information > Tile Configuration > **Assignment** > Confirmation

Register to SAP Fiori Launchpad

Assignment

*Site	cmbSDKTestSite
*Catalog	Sample Catalog
*Group	Sample Group

- Click finish on Confirmation tab and if everything is fine the popup below will be shown. Click OK to close this popup. With these steps we deploy our project on HCP and now we can continue to build our Fiori Mobile Application

Successfully Registered x

The application was successfully registered to SAP Fiori launchpad.

[Open the registered application](#)

[Open SAP Fiori launchpad](#)

OK

- Go to Services tab again, open Fiori Mobile service, and click on Go to Admin Console



Service: SAP Fiori Mobile - Overview

Enabled

Service Description

The mobile service for SAP Fiori is an end-to-end solution designed to support mobile users. Use the build/packaging service to transform web content into mobile apps, manage the app lifecycle, runtime services to support enterprise app security, and analytics services to provide insights into adoption, usage, and app performance.

Take Action


[Configure Fiori Mobile](#)

[Configure Mobile Packager](#)

[Go to Admin Console](#)

[Go to Mobile Place](#)

- Open Manage Plugins section and upload **cmbsdk-cordova** plugin as custom plugin. You can download latest plugin on this [link](#).



- Next manage your signing profiles. Open Manage Signing Profiles section and create new ones if you don't have already

Platform	Profile Name	Uploaded By / Generated By	Expiry Date
iOS	iOSSapAp...	Uploaded By [Red Bar]	May 27, 2020
Android	AndroidSa...	Generated By [Red Bar]	Jun 18, 2044
iOS	NAT_Daniel	Uploaded By [Red Bar]	Expired On May 11, 2018
Android	NAT	Generated By [Red Bar]	Expiry Date Oct 6, 2042

- Now open Manage Apps section and create New Application

Manage Apps

[+ New Application](#) [Categories](#)

- Select first option

What's Your Fiori App Scenario?

Tell us about the number of Fiori apps you want to put into a single binary



I want to create a local launchpad with only the apps I want to mobilize.

Choose this if you want to create a custom, local launchpad with multiple Fiori applications. We'll download the UI for the apps into the binary when we build it, so it's there when the app launches. You'll need Fiori 1.30+ compliant applications and be running the Fiori Server UI Add-on 2.0.



I want to mobilize an existing launchpad or Fiori application.

Choose this if you have a single Fiori URL you want to mobilize, or if you are not running the Fiori Server UI Add-on 2.0.

Previous

Next

Cancel

- Select your Fiori Cloud Edition as Fiori Server

Select Your Fiori Server

Fiori Server Name	Virtual Host with URL	Status
Fiori Cloud Edition	[REDACTED]	Available
GM4	[REDACTED]	Available


Previous Next Cancel

- Select application that we created before (with double click or drag&drop)

Define your Fiori Application

☒ Select from available Fiori Applications

Available Applications

 cmbSDK Fiori App: MyFirstFioriApp.MyFirstFioriApp

Selected Applications



--

☐ Upload advanced configuration file

File Name

Browse...

File Validation

Previous

Next

Cancel

- Set you application name and signing profiles. At the bottom of page you have question "Are you ready to build the application ?". Select "No, I would like to customize my application".

Build Your Fiori Application

152px X 152px

***Application Name**

cmbSDK Sample App

Uplo...

Connection Security

Users will be authenticated with SAML each time the application is used.

Build Options

☒ iOS Signing Profile: **IOSAppDev** Minimum OS Version: **11.0**

☒ Android Signing Profile: **AndroidAppDev** Minimum OS Version: **5.0**

☐ Enable Android and/or iOS project(s) download after build

☐ Enable verbose logging

☐ Build debug-enabled binaries

Note: If you would like to debug your Android application with Chrome and/or your iOS application with Safari, enable this option. For Android, your application will be automatically signed with an internal debug signing profile. For iOS, select a developer signing profile to sign your application to enable you to debug.

For iOS, an iOS signing profile must be selected to enable the build option.

Cached Content


☐ Clear cached content prior to initiating build

Note: SAP caches the SAPUI5 runtime referenced by your application in order to reduce build time. If you believe this content may have been updated since the last time an application was built referencing this SAP Fiori front-end server, enable this option.

Multimedia

Splash Screen - Portrait


1536px X 2048px



Upload

Splash Screen - Landscape

2048px X 1536px



Upload

Are you ready to build the application?

☐ Yes

☒ No, I would like to customize my application

(A red arrow points to the 'No, I would like to customize my application' radio button.)

Previous Next Cancel

- Window where we can continue with app customization will be opened. From here we will add plugin that we uploaded before and disable passcode screen. You can set some others parameters per your needs. Also important thing here is to save every change that will be made.

Insight

Details

Groups

Multimedia

Plugins

App Settings

Platforms

Categories

Owner info

Selected (0)

Recommended (0)

Public (2130)



Custom (1)

Select Platform

Search Plugins

Q

↕

Plugin ID	Platform	Version	Description	Last Updated	Actions
cmb-sdk-cordova-plugin		1.2.14	CMB Scanner Cordova Plugin	18th June 2018	<div><div>Add</div><div>View Details</div></div> 

Save

Delete

Insight

»

Details

»

Groups

»

Multimedia

»

Plugins

»

App Settings

»

Platforms

»

Categories

»

Owner info

Selected (1)

Recommended (0)

Public (2130)

Custom (1)

Select Platform

Search Plugins

Q

↕

Plugin ID	Platform	Version	Description	Last Updated On	Actions
cmb-sdlc-cordova-plugin		1.2.14	CMB Scanner Cordova Plugin	18th June 2019	

 Save

 Delete

Insight

»

Details

»

Groups

»

Multimedia

»

Plugins

»

App Settings

»

Platforms

»

Categories

»

Owner info

Security

Feature Management

Notifications

Logging

Connection Security

Users will be authenticated with S-MIL each time the application is used.

Application Passcode Policy

☒

Disable Passcode Screen

☐

Enforce Fiori application passcode

Minimum passcode length in characters

0

▼

Passcode expiration timeout in minutes

5

▼

Maximum retries

10

▼

Minimum unique characters

0

▼

☐

User must change passcode in days

30

▼

title: SAP Fiori Mobile (v2.1.x) ; ver: 2.7.x

42 / 47

☐ Allow default passcode

Passcode must contain at least one of the following character types

☐ Numeric (0-9)

☐ Lowercase alpha (a-z)

☐ Uppercase alpha (A-Z)



☐ Special (such as #, @, ~)

Application Security

Privacy Screen:

iOS and Android devices have app switchers that display screenshots of your apps. This is a possible privacy risk for apps that display sensitive information. To enhance the security of on-device data, SAP Fiori Client by default enables the Privacy Screen feature, which hides application content in the app switcher. On Android devices, the Privacy Screen plugin also prevents users from taking screenshots and sharing the screen. This feature is enabled by default.

☒ Disable Privacy Screen

- We are ready to build our mobile application and generate .ipa and .apk files. Navigate to Platforms and click **Build All** button if you want to build both iOS and Android platform together, or you can build one by one from Actions grid column.

Insight

»

Details

»

Groups

»

Multimedia

»

Plugins

»

App Settings

»

Platforms

»

Categories

»

Owner info

State	Debug Enabled	Operating System	Form Factor	App Version	Built On	Certificate Expiration	Actions
Ready to build		iOS	Tablet/Phone	1.0			<div>Build</div>
Ready to build		ANDROID	Tablet/Phone	1.0			<div>Build</div>

Build All

Your application is ready to be built!

Save

Delete

Build popup will be shown. Click Build button and wait while building process finish.

Build Summary

Application Information

Application Name:

cmbSDK Sample App

Build Options



iOS

Signing Profile:

iOSSapAppDev



Minimum OS Version:

11.0



Android

Signing Profile:

AndroidSapAppDev



Minimum OS Version:

5.0



Enable Android and/or iOS project(s) download after build



Enable verbose logging



Build debug-enabled binaries

Note: If you would like to debug your Android application with Chrome and/or your iOS application with Safari, enable this option. For Android, your application will be automatically signed with an internal debug signing profile. For iOS, select a developer signing profile to sign your application to enable you to debug.

For iOS, an iOS signing profile must be selected to enable the build option.

Cached Content



Clear cached content prior to initiating build

Note: SAP caches the SAPUI5 runtime referenced by your application in order to reduce build time. If you believe this content may have been updated since the last time an application was built referencing this SAP Fiori front-end server, enable this option.

Email Notification



Send me an email notification when my applications are built

 Build Cancel

- When building process is finished you can download binary (.ipa or .apk) file and install application on your mobile device

State	Debug Enabled	Operating System	Form Factor	App Version	Built On	Certificate	Actions
New Signed	⬇	ANDROID	Tablet/Phone	1.0	Jun 18, 2019		Edit Sign App Download Binary Set to trial Set to production Delete
New Signed	⬇	iOS	Tablet/Phone	1.0	Jun 18, 2019	5/27/202	Set to production Delete
Ready to build		iOS	Tablet/Phone	1.1		5/27/202	Delete
Ready to build		ANDROID	Tablet/Phone	1.1			Delete

Build All

Your application is ready to be built!


Save Delete

Licensing the SDK

If you plan to use the **cmbSDK** to do mobile scanning with a smartphone or a tablet (without the MX mobile terminal), the SDK requires the installation of a license key. Without a license key, the SDK will still operate, although scanned results will be blurred (the SDK will randomly replace characters in the scan result with an asterisk character).

Contact your Cognex Sales Representative for information on how to obtain a license key including trial licenses which can be used for 30 days to evaluate the SDK.

After obtaining your license key open `i18n.properties` file in your project on SAP WEB IDE service, and set your obtained keys.



Then go back to the *Component.js* file and check this code:

```
...  
  
var sdkKEY = "";  
if (Device.os.android)  
    sdkKEY = this.getModel("i18n").getProperty("MX_MOBILE_LICENSE_ANDROID");  
else  
    sdkKEY = this.getModel("i18n").getProperty("MX_MOBILE_LICENSE_iOS");  
  
cmbScanner.registerSDK(sdkKEY);  
  
...
```

You can see that you read this key from `i18n.properties` and call **cmbScanner.registerSDK** method to register SDK with your license key.